



A Benny Lee Company

RM SERIES

RACK MOUNT POWER SUPPLY

FEATURES

- Systems use proven DuraComm "Power Block" switching modules
- Modular design provides N+1 redundancy for certain models (see table below)
- Selectable 110 or 220 VAC inputs
- 19" width fits standard EIA rack
- Thermostatically controlled fans come on only when needed, extending fan life
- 80% typical efficiency means low heat output and low power costs
- Selectable metering option available measures voltage output and individual module current (models with "M" suffix)
- Output voltage is adjustable (see table below)



Depth - 7.5"
See Below for
Height & Weight



Front Panel with Meter

SPECIFICATIONS

Model Number	Output Current (Amps)	Output Voltage VDC	Input Voltage VAC	Panel Height	Weight (lbs)	N+1	Meters
RM-2512	25	13.8	110 or 220	3.5"	8.5	NO	NO
RM-2512M	25	13.8	110 or 220	3.5"	8.5	NO	YES
RM-5012	50	13.8	110 or 220	3.5"	9.5	YES	NO
RM-5012M	50	13.8	110 or 220	3.5"	9.5	YES	YES
RM-7512	75	13.8	110 or 220	7"	16.5	YES	NO
RM-7512M	75	13.8	110 or 220	7"	16.5	YES	YES
RM-10012	100	13.8	110 or 220	7"	17.5	YES	NO
RM-10012M	100	13.8	110 or 220	7"	17.5	YES	YES
RM-1224	12.5	27.5	110 or 220	3.5"	8.5	NO	NO
RM-1224M	12.5	27.5	110 or 220	3.5"	8.5	NO	YES
RM-2524	25	27.5	110 or 220	3.5"	9.5	YES	NO
RM-2524M	25	27.5	110 or 220	3.5"	9.5	YES	YES
RM-5024	50	27.5	110 or 220	7"	17.5	YES	NO
RM-5024M	50	27.5	110 or 220	7"	17.5	YES	YES
RM-548	5	48	110 or 220	3.5"	8.5	NO	NO
RM-548M	5	48	110 or 220	3.5"	8.5	NO	YES
RM-1248	12.5	48	110 or 220	3.5"	9.5	NO	NO
RM-1248M	12.5	48	110 or 220	3.5"	9.5	NO	YES
RM-2548	25	48	110 or 220	7"	17.5	YES	NO
RM-2548M	25	48	110 or 220	7"	17.5	YES	YES